



Switch Lite 16 PoE

Layer 2, PoE switch with (16) GbE RJ45 ports, including (8) 802.3at PoE+ ports.

The Switch Lite 16 PoE (USW Lite 16 PoE) is a fully managed switch with (16) GbE RJ45 ports, including (8) 802.3at PoE+ ports, and a 45W total PoE supply for your UniFi access points and other PoE devices. The USW Lite 16 PoE also offers an extensive suite of Layer 2 switching protocols, and can be monitored or configured from anywhere with the powerful, intuitive UniFi Network web application and mobile app.



Mechanical

Dimensions	191.7 x 185 x 43.7 mm (7.55 x 7.28 x 1.72")
Weight	1.2 kg (2.65 lb)

Hardware

Total Non-Blocking Line Rate	16 Gbps
Max. Power Consumption	15W
Power Method	Universal AC Input: 100-240VAC
Power Supply	Internal 60W AC/DC Power Supply
Networking Interfaces	(16) 10/100/1000 Mbps Ethernet RJ45
PoE Interfaces	(8) PoE+ IEEE 802.3af/at (Pins 1, 2+; 3, 6-)
Management Interface	Ethernet In-Band
Max PoE+ Wattage per Port by PSE	30W
Modes	SMB Layer 2 PoE Gigabit Ethernet Switch
Operating Temperature	-15 to 40° C (5 to 104° F)
Operating Humidity	10 - 90% Noncondensing
Certifications	CE, FCC, IC

LEDs

System	(1) Power, Blue/White Flashing White: Bootup in Progress Flashing Blue: Firmware Upgrading Steady White: Factory Defaults, Awaiting Adoption Steady Blue: Device is Adopted
Ethernet	Green: 1G, Amber: 10/100 Mbps
PoE	Amber: IEEE 802.3af/at



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2020 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, and UniFi are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.